



Certificate of Conformity

Certificate: 14059-1G Rev1

Master Contract: LC 1076058

Project: 14099

Date Issued: October 9, 2014

Issued to: **Fire by Design**
10624 South Eastern Ave., Suite A826
Henderson, Nevada,
89052, USA

Certification System Type 3
(ISO / IEC Guide 67)

The products listed below are eligible to bear the LabTest Certification Mark with adjacent indicators 'C' and 'US', and the subject area as shown below.



Issued by:


Certification Manager

PRODUCTS

- Outdoor Decorative Gas Appliance
- Model Nos.: AWEIS
- Ratings:
 - AM6-24-LP – Minimum 33,000 BTU/hr at 11" water column of liquid petroleum
 - AM6-24 – Minimum 28,500 BTU/hr at 7" water column of natural gas
 - AM6-24 & AM6-24-LP – 24VAC / 1.5A / 60HZ
 - ASC6-30-LP – Maximum 161,500 BTU/hr at 11" water column of liquid petroleum
 - ASC6-30 – Maximum 165,000 BTU/hr at 7" water column of natural gas
 - ASC6-30 & ASC6-30-LP - 24VAC / 1.5A / 60HZ

APPLICABLE REQUIREMENTS & SUBJECT AREA

- ANSI Z21.97: 2014 / CSA 2.41: 2014 - Outdoor Decorative Gas Appliances
- CAN / CSA C22.2 No. 3-M1988 (R2014) - Electrical Features of Fuel Burning Equipment

CONDITIONS OF ACCEPTABILITY

- permanently connected to a fixed fuel piping system and electrical power input
- Intended to be used outdoors only with heat shield and approved media installed
- Each model can be used with either natural gas or liquid petroleum.

The 'C' and 'US' indicators adjacent to the LabTest Certification Mark shall signify that the product has been evaluated by an accredited laboratory to the applicable CSA and UL Standards respectively. The subject area shall be displayed with the LabTest Certification Mark to identify the Standard Number, and Revision Level.